

# WWT JetReam™

## Drillable Reamer & Jetting Shoe



### Specifications

JetReam Model	450	550	700	758	858	958	1075	1175
Casing Size (inches)	4-1/2	5-1/2	7	7-5/8	8-5/8	9-5/8	10-3/4	11-3/4
Reamer OD (inches)	5-3/4	6-3/4	8-3/8	8-3/4	9-3/4	11-1/8	11-3/4	12-1/4
Minimum TFA (in <sup>2</sup> )	2.1	2.1	5.1	5.1	7.1	7.1	7.1	7.1

\*TFA in. With jetting feature TFA out is reduced until opening centerline at predetermined flow rate.

### Features and Benefits

- **Effective**
  - Patented embedded ceramic cutting elements provide effective reaming and movement of cuttings.
  - Ring of powerful jets help wash through cuttings and debris. Large center nozzle opens if needed.
- **Durable**
  - Rotate casing to ream down through trouble zones or past obstructions.
  - Tough polyurethane body with aluminum frame and ceramic cutters.
  - Steel frame and cutters on 4-1/2" and 5-1/2"
- **Efficient**
  - Fast drill-out with PDC or rock bits. Little or no metal in drill-out path.
  - Cost effective.
- **Modular**
  - Works well with the WWT FlexShoe.
  - Float installed separately above shoe.



WWT  
International

See how it works at  
[www.wwtinternational.com](http://www.wwtinternational.com)

PS008A