

# WWT Slider-Clamp Cable Protector

## WWT Slider-Clamp

- Fast & easy installation with standard 1-1/4" and 3/4" banding.
- Durable, downhole-proven materials protect cable and tubing from damage.
- 1/4" & 3/8" capillary tubing provisions for securing injection tubing.
- Centers cable and tubing in the wellbore.
- Fast & easy removal, with ability for product to be reused on most occasions, saves time and money on re-runs.

## HP Model

High performance polyurethane provides excellent protection for all applications. Cost-effective, durable and easily made in a variety of sizes and configurations.

## LF Model

Low friction proprietary polymer reduces sliding friction by up to 50%, while inside grips the pipe and cable. Perfect for running cables/lines into high-angle wells.



HP Model



LF Model



**WWT International**  
**Drilling Tools Services**

[www.wwtinternational.com](http://www.wwtinternational.com)

For more information,  
contact your local WWT sales  
representative or visit our  
website.

# WWT Slider-Clamp Specifications

Slider-Clamp Model*	Tubing Size	Cable Size	OD	Overall Length	Max Temp	Material	Banding
B-278-128R-LF	2-7/8"	1.28" Round	5.5"	5.5"	230°F	2-pc Low-Friction Polymer with Rubber ID	One 1-1/4" Band
B-278-163F-LF	2-7/8"	Up to 1.63" Wide Flat	4.4"	5.5"	230°F	2-pc Low-Friction Polymer with Rubber ID	One 1-1/4" Band
B2-278-163F-HP	2-7/8"	Up to 1.63" Wide Flat	4.4"	5.9"	250°F+	1-pc Polyurethane	Two 3/4" Bands
B2-278-150F-HP	2-7/8"	Up to 1.50" Wide Flat	4.4"	5.9"	250°F+	1-pc Polyurethane	Two 3/4" Bands



*\*For information only. Specifications subject to change. Other sizes available upon request.*



**WWT International**  
**Drilling Tools Services**  
[www.wwtinternational.com](http://www.wwtinternational.com)

For more information,  
 contact your local WWT sales  
 representative, or email  
[sbanks@wwtco.com](mailto:sbanks@wwtco.com)