

WWT Coiled Tubing Tractors™



Over 2,000,000 Feet Tractored

- Greater pulling power than any other extended reach tool, enabling the delivery of heavy tool strings to the outer zones of extended-reach wells.
- Features an exclusive design that allows for ball drop or e-line pass through flexibility for tools positioned below the WWT Tractor.

Wellbore Cleanout • Acidizing • Logging • N2 Lift • Milling • Perforating

Tractor Model	212L	2125	312	350 ERG	350 EEG	470 ERG
Maximum OD (in)	2.125	2.125	3.125	3.500	3.500	4.750
Minimum ID (in)	0.368	N/A	0.688	0.500	0.500	0.75
*Length (ft)	20	22	9.5	24	24	27.5
**Operational Wellbore or Range (in) OH = Openhole CSG = Casing	6.125 OH	4.5 to 7 CSG 6 to 8.5 OH	9.5 to 7 CSG	4.5 to 7 CSG 6.125 OH	4.5 CSG 8.5 OH	7 CSG 6.125 OH
Maximum Operational Pressure (psid)	2,200	2,200	1,500	1,700	1,700	1,700
Fluid Consumption at 750 ft/hr (gpm)	6	6	7	7	7	15
Maximum Pull (lbs)	3,200	3,200	6,250	9,200	9,200	14,500
Maximum Speed (ft/hr)	1,000	1,000	750	900	900	1,000
Maximum Overpull (lbs)	12,000	13,000	95,000	62,000	62,000	62,000
Connection	1-1/2 AMMT	1-1/2 AMMT	2-3/8 PAC	2-3/8 PAC	2-3/8 PAC	2-3/8 PAC
***Maximum Temperature(°F)	392					
Acid & H2S Resistant	Yes (NACE Compliant)					
Materials	Inconel, BeCu, Steel, and Stainless Steel					

^{*} Length of Tractor subject to change ** Range can be configured for customer requirements *** Can be configured to perform in 35% based on application H2S up to 392°F

WWT International Coiled Tubing Services supports your operational effort from start to finish.

- A truly full service on-site mobilization, including a complete standalone workshop for remote redress and inventory support.
- Equipped with a complete set of diagnostic and testing equipment for fast adaptation to changing well conditions.
- Free well analysis and application review available upon request.

Scan this code to find out more about WWT Coiled Tubing Tractors including case histories, or visit our website at **www.wwtco.com.**











