

WWT ReamGuide™

Drillable Reamer Shoe



Specifications

ReamGuide Model	450	550	700	758	858	958	1075	1175
Casing Size (inches)	4-1/2	5-1/2	7	7-5/8	8-5/8	9-5/8	10-3/4	11-3/4
Reamer OD (inches)	5-3/4	6-3/4	8-3/8	8-3/4	9-3/4	11-1/8	11-3/4	12-1/4
Minimum TFA (in ²)	2.1	2.1	5.1	5.1	7.1	7.1	7.1	7.1

Features and Benefits

- **Durable**
 - Rotate casing to ream down through trouble zones or past obstructions
 - Tough polyurethane or cement composite body with aluminum frame holding cutters.
- **Effective**
 - Patented embedded ceramic cutting elements provide effective reaming and movement of cuttings
- **Efficient**
 - Made from aluminum and polyurethane or cement composite.
 - No metal in drill-out path in most cases.
 - Cost effective.
- **Modular.**
 - Works well with the WWT FlexShoe.
 - Can be used as a stand-alone product.
 - Float installed separately above shoe



WWT
International

See how it works at

www.wwtinternational.com

Revised 1/4/17

©2016 WWT North America Holding Inc. All rights reserved. WWT FLX is a trademark of WWT North America Holdings Inc. Specifications may change without notice. US Patent number 9,702,197