

Tractor Model	212L	212S	312	350 ERG	350 EEG	350 ERT	470 ERG
Maximum OD (in)	2.125	2.125	3.125	3.500	3.500	3.500	4.750
Minimum ID (in)	0.368	N/A	0.688	0.500	0.500	0.500	0.75
*Length (ft)	20	22	12.6	24	24	14	27.5
**Operational Wellbore or Range (in) OH = Openhole CSG = Casing	6.125 OH	4.5 to 7 CSG 6 to 8.5 OH	4.5 to 7 CSG	4.5 to 7 CSG 6.125 OH	4.5 CSG 8.5 OH	6.625 CSG	7 CSG 6.125 OH
Maximum Operational Pressure (psid)	2,200	2,200	1,500	1,700	1,700	1,700	1,700
Fluid Consumption at 750 ft/hr (gpm)	6	6	7	7	7	7	15
Maximum Pull (lbs)	3,200	3,200	6,250	9,200	9,200	10,200 single 20,400 tandem	14,500
Maximum Speed (ft/hr)	1,000	1,000	750	900	900	750	1,000
Maximum Overpull (lbs)	12,000	13,000	95,000	62,000	62,000	62,000	62,000
Connection	1-1/2 AMMT	1-1/2 AMMT	2-3/8 PAC	2-3/8 PAC	2-3/8 PAC	2-3/8 PAC	2-3/8 PAC
***Maximum Temperature(°F)	300						
Acid Resistant	Yes						
Materials	Inconel, BeCu, Steel, and Stainless Steel						

* Length of Tractor subject to change based on application

** Range can be configured for customer requirements

*** Can be configured to perform in 35% H₂S up to 392°F